

d-Copia

4514MFplus Productivity and quality with respect for the environment

The Olivetti d-Copia 4513MFplus, d-Copia 4514MFplus, d-Copia 5514MF, and d-Copia 6014MF are a range of mid-volume multifunctional models offering print speeds of 45 ppm, 55 ppm, and 60 ppm. They are the ideal choice for medium to large-sized workgroups requiring a compact, easy-to-use system with decidedly low running costs.

Document throughput is optimized and
facilitated by the large color control panel with
customization support, and by the on-board
JaWS software development platform. What's
more, long-life components provide
exceptional reliability while contributing
towards reducing both operating and
environmental impact.

The d-Copia 5514MF and d-Copia 6014MF are the top of the range in terms of speed, printing, and copying at 55 ppm and 60 ppm models, respectively. They are built for heavy-duty printing and scanning work with the originals feeder supporting single-pass duplex scanning with a throughput of up to 100 scanned pages per minute.

Mono Multifunctional Digital Systems	
SPEED	*
QUALITY	
COLOUR TOUCH SCREEN	□
ECO-FRIENDLY	0
COMPACT	7 K
SECURITY	②
WI-FI AND WI-FI DIRECT *	?

*optional



UP TO 45, 55 & 60 PPM A4 (See Technical Specifications for A3 speed) | 1,200 x 1,200 DPI PRINT RESOLUTION
7" COLOUR TOUCH SCREEN | COMPACT DESIGN | AUTOMATIC SINGLE PASS DUPLEX FEEDER (d-Copia 5514MF AND
d-Copia 6014MF ONLY) | JAWS PROGRAMMING PLATFORM | SEARCHABLE PDF (with Scan Extension Kit)



SPECIFICATIONS

Web Solutions)

Up to 45 ppm A4

Approx 16 secs or less

Approx 5.9 secs or less Approx 7 secs or less

Standard IGB, Max. 3GB + SSD 128GB

Base Unit approx 22.5 kg Base Unit: 475 x 476 x 575mm AC 220 V 240 V, 50/60 Hz

Approx 7 secs or less

1 (for IB-36); 100 dept codes

630 W/ 652W

54 dB(A) LpA 30 dB(A) LPA

Printer/Scanner/Copier Mono Laser; JAWS software development platform (Java and

Up to 22.5 ppm A4 ARM Cortex-A9 Dual core 1.2GHz + ARM Cortex-M3 100MHz

1200 x 1,200 dpi (print), 600 x 600 dpi (scan/copy) 7" Colour Touch Screen, Speakers for job not ifications, tiltable

USB Interface connector: 1 (Hi-Speed USB); Network interface: 1 (10 Base-T/IOO Base-TX/I OOO Base-T);

Interface (optional): 1 (for IB-50 /lB-51); Wirel ess LAN (optional):

1 00-sheet, 60 — 220 g/m2 A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm - 216 x 356 mm)
500-sheet, 60 - 120 g/m2 , A4, A5, A6, B5, B6, Letter, Legal, Custom (140 x 148 mm - 216 x 356 mm);
500-sheet, 60 — 120 g/m2 , A4, A5, A6, B5, B6, Letter, Legal,

75-sheet RADF 50-120 g/m2, A4, A5, B5, Letter, Legal, Custom (1 05 x 148mm - 21 6 x 356 mm)

PCL 6 (Sc/KL), KPDL 3 (PostScript 3-compatible), PDF Direct Print, XPS Direct Print, AES Support, TIFF/JPEG Direct Print Support, open xps, Line Printer, IBM Proprinter X24E, Epson LQ-850 All current Windows Operating Systems, Mac OS X Version 10.8

93 scalable fonts (PCL6/KPDL3), 8 fonts (Windows), 1 Bitmap

and 1 two-dimensional barcode type (PDF-417) Olivetti Mobile Print for iOS and Android, AirPrint, Direct Wi-Fi

(optional), Google Cloud Print PDF direct printing, IPP printing, E-mail printing, WSD printing, SSL-protected printing, IPsec, SNMPv3

Custom (92 x 1 62 mm - 216 x 356 mm); (max 4 additional drawers) 2,600 sheets, A4 (with additional drawers)

Max 250 sheets face-down 60-120 g/m2, A4, A5, B5, Letter, Legal

font, 45 one-dimensional barcode types

GENER AL

Type:

Technology:
Print/Copy Speed (per minute):
Duplex Print/Copy Speed (per minute):

Resolution: Operator Panel: Warm-up Time: First Print-out Time:

First Copy Time from DP: First Copy Time from Platen:

Memory: Standard Interfaces: Embedded Counter:

Duty Cycle (Pages/Month): Dimensions (W x D x H):

Power Supply: Energy Consumption Printing/Copying: Energy Consumption in Ready Mode:

Energy Consumption in Standby: Noise Levels (according to ISO 7779/1SO 9296):

Printing: TEC (kWh/wk):

PAPER HANDLING

Universal Bypass:

Standard Drawer:

PF-3110 Paper Drawer, optional:

Paper Input Capacity, max: Duplex Automatic Originals Feeder: Paper Output Capacity: Standard Duplex Functionality:

PRINT FUNCTIONS

Print Speed per Minute : Emulations:

Operating Systems:

Fonts / Barcodes:

Mobile Printing Support:

Printing Functions:

COPY FUNCTIONS

Copy Speed, max:

Reduction / Enlargement ratios:

Originals Format, max:

Continuous Copying:

Image Adjustment: Other Functions:

4 5 ppm A4

Up to 45 ppm A4

or later, UNIX, LINUX

7 Reductions/5 Enlargements

Α4 1 - 999

25 - 400% in steps of 1% Text + Photo, Photo, Text, Map, Printed Documents

Electronic sort, ID Card Copy, 2 in 1, 4 in 1, Automatic drawer

selection, Skip blank page

SCAN FUNCTIONS

Functionalities:

Scan Speed:

Scan Resolution: Scan Format, max: Originals recognised: Image Formats: Compression Method: Other Features: Scan to Email (SMTP) Scan to FTP over SSL, Scan to SMB, Scan to USB Host, Scan to Twain Box (network), WSDJ WIA

Up to 60 ipm (A4, 300 dpi, mono

40 ipm (A4 300 dpi, colour); Duplex: 26 ipm (A4, 300 dpi mono),

17 ipm (A4 300 dpi, colour) 600 dpi, 400 dpi, 300 dpi, 200 dpi, 256 grey scales

Text, Photo, Text+Photo, Light Text/Fine line, OCR-optimised Text TIFF/JPEG, xps, open xps, PDF, PDF/A, PDF/A-1 a/b, PDF/A-2a/b/u, Encrypted PDE High compression PDF MMR/JPEG

Banner scan, Colour scan, Integrated address book, Active Directory

support, Encrypted data transfer, Simultaneous multi-send (e-mail, fax, FTP/SMB folder, prints), Blank

CONSUMABLES

Average toner yield is compliant with ISO/IEC 19752 standard

Black Toner Cartridge (B1286) Up to 14.500 A4 pages (initial toner up to 6.000 pages)

Maintenance Kit (B1288) Up to 300,000 pages Sheet Feeder Maintenance Kit (B1144)Up to 200,000 pages

Staple Cartridges (B1189) n/a

OPTIONS

Paper Drawer (B3637) Semi-automatic Stapler (B3625) CB-365 L (B3687) CB-360 H CB-360 H 18368) Additional Memory: HD-6 (B4369) HD_7 (B4844) Data Security Kit (E) (B5679) HD-6, HD-7 or SD Card necessary Scan Extension Kit (A) (B4498) HD-6, HD-7 or SD Card necessary IB-36 (B3406) IB-50 (B4805) IB-51 (B4933) UG-33 (B8403) USB IC-Card Reader + Card Authentication Kit (B) Card Reader Holder 10 (B4845)

PF-3110, 500 sheets (max 4 optional drawers)

Cabinet with paper compartment (low) 38 cm x 41 cm x 25 cm Cabinet with paper compartment (high) 38 cm x 41 cm x 51 cm DDR3; MD3-10241 GB; MDDR3-2GB SSD 32GB Hard disk for easier document management

SSD 128GB Hard disk for easier document management For d-Copia 4514MFPlus/ d-Copia 5514MF/ d-Copia 6014MF also compliant with ISO 15408 (Common Criteria) EAL2 security level Se archable PDF scanning (OCR integrated), MS Office (docx, xlsx,

Wireless network interface (802.11 b/g/n) with Wi-Fi Direct Gigabit Ethernet 10BaseT/100BaseTX/1000BaseT Wireless network interface (802.11 b/g/n)

ThinPrint support

Support for various types of authentication / card / badge reader Plastic holder for incorporating badge reader on control panel

Performance relates to use of the product under optimal conditions.

Right reserved to modify te chnical specifications

Registered trademarks are the property of their respective owners. d-Copia 4513MFplus-4**5**4MFplus-5514MF-6014MF are distributed by Olivetti S.p.A.

(09/2018) - Code: 49743-00-w







