

ECONOMICAL. ECOLOGICAL. ECOSYS TECHNOLOGY.



The ECOSYS P8060cdn brings power and performance to high-quality color printing. With output speeds up to 60 pages per minute, advanced finishing, vivid 1200 x 1200 dpi color and flexible configurations, the ECOSYS P8060cdn easily tackles both complex printing and day-to-day business requirements with ease. Kyocera's customizable Business Applications maximize efficiency, empowering your workforce to leverage printed information how, when and where they need it. Add to that Kyocera's award-winning, ultra-reliability and unique long-life technology, and you have a powerful document solution that delivers exceptional results.

- > Impactful Color and Black and White Imaging at Speeds up to 60 Pages per Minute in Black and 55 Pages per Minute in Color
- > Flexible Media Support and Paper Sizes up to 12" x 48"
- > High Capacity Paper Handling up to 7,150 Sheets

- > Customizable 9" Color Touch Screen with Intuitive, Tablet-Like Home Screen
- > HyPAS Capable to Run Kyocera Business Applications for Printing
- Advanced Finishing Options for Professional Output, Including a
 4,000 Sheet External Finisher and Optional Booklet Folding
- > Standard USB Host Interface for On-the-Go Printing
- > Convenient Wireless Printing
- > Apple AirPrint®, Google Cloud Print™ and KYOCERA Mobile Print Compatible for a Mobile Printing Solution
- > Standard Near Field Communication (NFC) for Android and Wi-Fi Direct Provides Added Smart Device Convenience
- > KYOCERA Fleet Services, a Secure Cloud-Based Monitoring System, Optimizes Device Uptime and Reduces Costs





ECOSYS P8060cdn

BASIC SPECIFICATIONS

Configuration: A3 Color Printer

Pages Per Minute:

Black - Letter: 60 ppm, Legal: 36 ppm, Ledger: 30 ppm,

12" x 18": 30 ppm

Color - Letter: 55 ppm, Legal: 33 ppm, Ledger: 27 ppm, 12" x 18": 27 ppm

Warm-Up Time: 17 Seconds or Less (Power On)

First Page Out: Print: 3.8 Seconds Black, 5.1 Seconds Color

Display: 9" LCD Color Touch Screen Control Panel

Resolution: 600 x 600 dpi; 9600 dpi x 600 dpi; 1200 x 1200 dpi

Memory / Hard Disk Drive:

4 GB RAM / 8 GB SSD / 320 GB HDD Standard

Duplex: Standard Stackless Duplex Supports Statement to 12" x 18", 14 lb Bond - 166 lb Index (52 - 300gsm) Standard Output Tray: Statement - 12" x 18" / 500 Sheets;

up to 12" x 48" Banner (Single Sheet)

Electrical Requirements: 120V. 60Hz. 12A: 220-240V: 50/60Hz. 7.2A

Typical Electricity Consumption (TEC):

120V: 3.19 kWh/week; 220-240V: 3.14 kWh/week

Dimensions: 23.7" W x 26.2" D x 31.1" H

Weight: 196 lbs

Maximum Monthly Duty Cycle: 250,000 Pages per Month

Standard Paper Sources: Dual 500 Sheet Travs. 150 Sheet MPT Optional Paper Sources: Dual 500 Sheet Trays (PF-7100), Dual 1,500 Sheet Trays (PF-7110); Side LCT: 3,000 Sheet Capacity Tray (PF-7120)1

Paper Capacity: Standard: 1,150 Sheets; Maximum: 7,150 Sheets Paper Size: Tray 1: 5.5" x 8.5" - 8.5" x 14" (Statement to Legal);
Tray 2: 5.5" x 8.5" - 12" x 18"; Custom Size; PF-7100:
5.5" x 8.5" - 12" x 18"; PF-7110, PF-7120: 8.5" x 11";
MPT: 5.5" x 8.5" - 12" x 18" (Multiple Sheets); Up to 12" x 48" Banner (Single Sheet)

Paper Weight: Trays / MPT: 14 lb Bond - 166 lb Index (52 – 300gsm)

Standard Output Tray Capacity: 500 Sheets

Input Materials: Standard / Optional Tray: Plain Paper, Bond, Vellum, Recycled, Preprinted, Cardstock, Color, Prepunched, Letterhead, Envelope, Thick, High Quality, Custom (Duplex: Same as Simplex); MPT: Plain Paper, Bond, Vellum, Recycled, Preprinted, Cardstock, Color, Prepunched, Letterhead, Envelope, Thick, High Quality, Transparency (OHP film), Coated, Index Tab Dividers

Standard: Local Authentication, Network Authentication, Encrypted Communication (IPsec, HTTPS, LDAP over SSL, SMTP over SSL, POP over SSL, FTP over SSL, SNMPv3) Optional: Data Security Kit(E): HDD Overwrite Mode, Data Encryption

PRINT SPECIFICATIONS

Standard Controller: Freescale QorIQ T1024 (Dual Core) / 1.2GHz PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL/PCL-5c), KPDL3 (Compatible with PostScript3), PDF, XPS/OpenXPS, TIFF, JPEG, IBM Proprinter, LinePrinter, LO-850

Fonts: 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap Windows OS Compatibility: Windows 10, Windows 8.1, Windows 8, Windows 7, Windows Vista, Windows Server 2012/R, Windows Server 2008/R2

Mac OS Compatibility: Apple Macintosh requires OS X v10.5

Mobile Printing: Apple AirPrint®, Google Cloud Print™, KYOCERA Mobile Print

Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB Host Interfaces, 2 Expansion Slots, Wireless LAN (communication distance 98.5 feet)

Optional: 10/100/1000BaseTX (IB-50 for Dual NIC), IEEE 802.11 b/g/n (IB-51 for Wireless LAN Interface - communication distance 328.1 feet)

Network Print and Supported Protocols: TCP/IP, NetBEUI, IPv4, IPv6, IPsec, HTTP, LPD, FTP, IPP, RawPort, LLTD, SNTP, DHCP, SMTP, POP3, DNS, SNMPv1/v2

Drivers: KX Driver, KX (XPS) Driver, PCL Mini Driver, KPDL Mini Driver, Status Monitor, Novell NDPS, Common Profile, Output to PDF, Security Watermark, Color Optimizer/Easy Color Adjustment, MAC Driver, Linux Driver, Windows Inbox Driver, KX PRESCRIBE Macro Generator Utilities: KYOCERA Net Direct Print, KYOCERA Print Center, KYOCERA Net Admin, KYOCERA Net Viewer, Quick Setup, Software Management Service, Upgrade Studio, Web Package Builder, Web Package Maker, Removal Tool, Wi-Fi Setup Tool, Command Center RX

OUTPUT & FINISHING OPTIONS OPTIONAL 1.000 SHEET FINISHER DF-7120

Stack / Staple Capacity: Main Tray: 1,000 Sheets / 50 Sheets

(up to 24 lb Bond [90gsm]) Paper Size: 5.5" x 8.5" - 12" x 18"

Paper Weight: 14 lb Bond - 166 lb Index (52 – 300gsm)

Edge Staple Position:

3 Positions: Top Left, Bottom Left, Center Bind Optional Punch: PH-A 2 and 3 Hole Punch Unit, Supports 5.5×8.5 " - 12" x 18"; 14 lb Bond - 166 lb Index (52 – 300gsm)

Dimensions: 21.57" W x 24.35" D x 41.34" H

OPTIONAL 4,000 SHEET FINISHER DF-7110 3

Stack / Staple Capacity: Main Tray (A): 4,000 Sheets; Sub Tray (B): 200 Sheets / 65 Sheets (up to 24 lb Bond [90gsm]) Paper Size: 5.5" x 8.5" - 12" x 18"

Paper Weight: 14 lb Bond - 166 lb Index (52 - 300gsm) Edge Staple Position: 3 Positions: Top Left, Bottom Left,

Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 5.5" x 8.5" - 12" x 18"; 14 lb Bond -166 lb Index (52 - 300gsm) Dimensions: 23.91" W x 26.32" D x 41.78" H

Optional Booklet Folder / Tri-fold Unit4: BF-730 Booklet Folder supports 8.5" x 11", 8.5" x 14", 11" x 17"; Fold booklet stapl $16\ lb$ – $24\ lb$ Bond (60 – $90\mbox{gsm})$ $16\mbox{ sheets; }25\ lb$ – $28\ lb$ Bond (91 - 105gsm) 13 sheets; Fold booklet no staple: 16 lb -24 lb Bond (60 - 90gsm) 5 sheets; 25 lb Bond - 72 lb Index (91 - 120gsm) 3 sheets; 32 lb Bond - 110 lb Cover (121 - 256gsm) 1 sheet; Trifold supports 8.5" x 11" only: 16 lb – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets; 16 lb – 28 lb Bond (60 – 105gsm) 1 sheet

Optional Multi-Bin Mailbox4: MT-730(B) includes 7 Trays; Supports 16 lb Bond - 90 lb Index (60 – 163gsm); Stack Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11";

50 Sheets: 8.5" x 14", 11" x 17" ADDITIONAL OPTIONS

Bridge Unit Attachment Kit (AK-7100), Banner Guide 10, Card Authentication Kit (B), Gigabit NIC (IB-50), Wireless LAN IEEE 802.11b/g/n (IB-51), ThinPrint (UG-33), Emulation (UG-34), Document Tray (DT-7100), Keyboard Holder 10, Data Security Kit (E), Numeric Keypad (NK-7100), Job Separator (JS-7100)

- 1 Requires PF-7100 or PF-7110
- Only 1 Output Option can be installed
- ³ Requires Bridge Unit Attachment Kit (AK-7100)
- ⁴Requires DF-7110

ONLY FROM KYOCERA

KYOCERA Document Solutions is a global leader in the digital imaging industry, with an award-winning line of document solutions that consistently set the standard for high performance, superior image quality, enhanced workflow applications, ease-of-use and durability.

Looking to streamline your document workflow? KYOCERA offers a robust portfolio of Business Applications that seamlessly and securely integrate with our MFPs and Printers. To learn more about which Business Applications are right for your business, visit the Solutions section on our website.*

*Compatibility will vary by model.

Specifications and design are subject to change without notice. For the latest on connectivity visit usa.kyoceradocumentsolutions.com. ECOSYS, PRESCRIBE, Command Center RX and KYOCERA Mobile Print are trademarks of the KYOCERA Companies.

Apple, Mac and AirPrint are registered trademarks of Apple, Inc. All other trademarks are the property of their respective owners.

KYOCERA Document Solutions America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA ©2017 KYOCERA Document Solutions America, Inc. All rights reserved. IC# 855D400626

















