

> PRINT > COPY > SCAN > FAX

ECOSYS M4125idn

MONOCHROME MULTIFUNCTIONAL FOR A4/A3 FORMAT

RICH FEATURE. AFFORDABLE PRICE.



- > Up to 25/12 pages A4/A3 per minute
- > Highly productive, professional print, copy, colour scan and fax functionality
- > Minimum installation and operation requirements

- > Easy to use full colour touch panel with wizard-style navigation
- > Low power consumption saves energy
- > Long-life components provide unprecedented efficiency and reliability
- > HyPAS[™] solution platform enables powerful customisations





CCOSYS* ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you

GENERAL

Technology: KYOCERA ECOSYS, Laser, Monochrome, HyPAS™ solution platform

HyPA3 ™ Solution platform Operation panel: 109.2 mm (4.3 inch), full-colour touch panel display, speaker for job notification Type: Desktop Engine speed: Up to 25/12 pages A4/A3 per minute.

Duplex print speed: 22 page per minute, A4 Duplex copy speed: 22 page per minute, A4 **Resolution:** 1200 x 1200 dpi (print), 600 x 600 dpi (scan/copy)

(scan/copy)

Warm-up time: Approx. 20 seconds or less
Time to first print: Approx. 5.8 seconds or less
Time to first copy: Approx. 7.0 seconds or less
Time to first copy: Approx. 7.0 seconds or less
Time to first copy: Approx. 7.0 seconds or less
Time to first copy: Approx. 7.0 seconds or less
Time to first copy: Approx. 7.0 seconds or less
Topy: Approx. 5.8 seconds or less (Platen Cover)
CPU: ARM Cortex-Ap Dual core 1.26Hz
Memory: Standard 16B, Max. 3GB + 1.28GB SSD
Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host
Interface, Gigabit Ethernet (10BaseT/100BaseTX/100B

Document Processor)

Weight: Approx. 49 kg (with standard Document Processor)
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption

Printing: 410 W Copying: 410 W Low power mode: 4 Ready mode: 65 W : 45 W

Sleep-mode: 0.5 W Noise (sound pressure level: ISO 7779/ISO 9296) Copying/Printing: 49 dB (A) Stand-by: 34 dB (A)

Safety standards: TÜV/GS, CE
This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

A5, B5, Letter, Legal, Custom (140 x 182 to 297 x 432 mm), Simplex scan 45–160 g/m², Duplex scan 50–120 g/m² **Output capacity:** Max. 300 sheets: 250 sheets face-down (Main Tray) plus 50 sheets (standard Job Separator Tray)

PRINT FUNCTIONS

Controller language: PRESCRIBE II e

Emulations: PCL6 (Se/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and Open XR3 frome OS Openating systems: All current Windows operating systems,

Operating stystems: All current Windows operating systems, MAC OS X Version 10. or higher, Unix, Linux, operating systems on request Fonts/barcodes: 101 outline fonts (PCL 6, KPDL 3, Windows Vista), 18 litmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417) Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPy3, quick copy, proof and hold, private print, job storage and job management functionality Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi

COPY FUNCTIONS

Max. original size: A3/Ledger

max. original size: A3/Leager
Continuous copying: 1–999
Zoom range: 25–400% in 1% steps
Preset magnification ratios: 5 Reductions / 5 Enlargements
Exposure mode: Auto, manual: 7 steps
Image adjustments: Text + Photo, Photo, Text, Map,
Printed document
Features: Scan-once-copy-many, electronic sort, 2in1, 4in1,
igh reserve priority print, program auto duples copy, split job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change (PF-470 or PF-471 is required), copy density control, Prevent Bleed-Through, ID card copy, Skip blank page

SCAN FUNCTIONS

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN, WIA , WSD scan **Scan speed:** 50 ipm (300 dpi, A4, b/w), 50 ipm (300 dpi,

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales per colour) **Max. scan size:** A3, Ledger

Max. Staff size: A, Ledger
Original recognition: Text, photo, text + photo, light text,
optimised for OCR
File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted
PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u
Compression method: MMR/JPEG

Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip

K FUNCTIONS (OPTIONAL)

Compatibility: ITU -T Super Ga Modem speed: Max. 33.6 kbps
Transmission speed: Max. 33.6 kbps
Scanning speed: 2.0 seconds or less
Address book: 200 entries

Scanning density:
Normal: 8 dot/mm x 3.85 line/mm (200 x 100 dpi)
Fine: 8 dot/mm x 77 line/mm (200 x 200 dpi)
Superfine: 8 dot/mm x 15.4 line/mm (200 x 400 dpi) Ultrafine: 16 dot/mm x 15.4 line/mm (400 x 400 dpi)

Halftone: 256 grey scales

Maximum original size: A3, Ledger

Compression method: JBIG, MMR, MR, MH Memory reception: 700 sheets or more Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

CONSUMABLES

Average continuous toner yield in accordance with

TK-6115 Toner Kit: Microfine toner black for 15,000 pages A4, Capacity of starter toner is 3,000 pages A4

OPTIONS

Fax System 13
Paper handling
PF-470 Paper feeder: Max. 500 sheets; 60–163 g/m²; A3,
A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm) A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 422 mm)
PF-471 Paper feeder: Max. 1,000 sheets; 60–163 g/m²; A3,
A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)
Security: Data security kit (E):
Memory upgrade: DDR3 1GB/2GB
HD-6: SSD 32 GB for easy document management
HD-7: SSD 128 GB for easy document management
SD card: for printing forms, fonts, logos, macro storage and for HyPASTM applications
USB Flash Memory: Supports direct printing and scanning of PDF, XPS, IT FF, IPEG files via USB Host interface
UG-33: ThinPrint support

UG-33: ThinPrint support
USB IC Card Reader + Card Authentication Kit (B): Support
for various authentication keys available. The card holder
is standard

Scan extension Kit (A) AC: Scan to searchable PDF (embedded OCR) or to MS Office (HDD, SSD or SD-card is needed)

Optional interface

Optional interface
IB-36: Wireless LAN (802.11b/g/n) with Wi-Fi Direct
IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/
1,000 BaseT
IB-51: Wireless LAN Interface (802.11b/g/n)

IB-51: Wireless LAN Interface (802.11D/g/n)
CB-470 Cabinet: Wooden desk with storage capacity, including castors (wheels)
CB-471 Base Unit: Wooden base for height increase (to be used only with PF-470 or PF-471)
CB-472 Cabinet: Metal desk with storage capacity, including castors (wheels)
CB-473 Base Unit: Metal base for height increase (to be used only with PF-473 or PF-4731)

(to be used only with PF-470 or PF-471)

WARRANTY

1-year warranty as standard.** KYOCERA guarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.













KYOCERA Document Solutions Europe B.V Bloemlaan 4 – 2132NP Hoofddorp – The Netherlands Tel +31 (0)20 6540 000 - Fax +31(0)20 653 1256 www.kyoceradocumentsolutions.eu - info@deu.kyocera.com

KYOCERA Document Solutions Inc. - 2-28, 1-Chome - Tamatsukuri Chuo-Ku - Osaka 540-8585 - Japan - www.kyoceradocumentsolutions.com

- * KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.
- ** Depending on the country

