Datasheet



HP PageWide Managed Color MFP P77940dns

HP Managed MFPs and printers are optimized for managed environments. Offering increased monthly page volumes and fewer interventions, this portfolio of products can help reduce printing and copying costs. See your HP Authorized Reseller for details.

Print Speed:Letter: Up to 40 ppm black; Up to 40 ppm color; First Page Out: As fast as 7.80 sec black; As fast as 8.02 sec color

Scan Resolution:Hardware: Up to 600 ppi; Optical: Up to 600 ppi

Standard Connectivity: 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket
Paper Handling:550-sheet Universal Input Tray; 100-sheet

Paper Handling:550-sheet Universal Input Tray; 100-sheet multi-purpose tray; 500-sheet face-down output bin Duty Cycle:Monthly, letter: Up to 150,000 pages

















Affordable color printing for every office

- Depend on lasting value. Get the results you expect for a game-changing low color cost per page.
- Print even faster—and save even more per page—by setting this printer to General Office mode.3
- Help keep energy costs down with the most efficient MFP in its class.2

Minimal interruptions. Maximum uptime.

- Minimize interruptions with an HP PageWide MFP designed for less maintenance than laser competitors.4
- Print speeds up to 50% faster than competitors—as fast as 60 ppm in color and black-and-white.6
- Print Microsoft® Word and PowerPoint® files with a USB port that quickly recognizes, formats, and prints.6
- Organize, staple, and collate documents with in-line finishing that helps you save time and look professional.

The world's most secure printing1

- A suite of embedded security features help protect your printer from being an entry point for attacks.
- Protect information on the MFP and in transit over the network.7
- Monitor activity to detect and stop attacks, then automatically reboot with run-time intrusion detection.
- Whitelisting checks firmware during startup to help ensure it's authentic, good code—digitally signed by HP.

Designed with the environment in mind

- With HP Sure Start, each printer regularly checks its operating code and repairs itself from attempted hacks.
- This MFP meets rigorous standards for ISO class 5 clean rooms—perfect for sensitive environments.
- Help reduce your impact. Count on easy cartridge recycling at no charge through HP Planet Partners.8
- Keep noise to a minimum with an MFP designed to be quiet. Place it near people without disrupting work.

Datasheet | HP PageWide Managed Color MFP P77940dns HP PageWide Managed Color MFP P77940dns Specifications Table

Functions / Multitasking Supported	Print, copy, scan, fax (optional) / Yes	Media Sizes Custom	HCI: LTR,; A4
Print Speed	A4: Up to 40 ppm; Letter: Up to 40 ppm black; Up to 40 ppm; Letter: Up to 40 ppm colỗr First Page Out: As fast as 8 sec black; As fast as 8.3 sec coloró	Paper Handling	550-sheet Universal Input Tray; 100-sheet multi-purpose tray; 500-sheet face-down output bin; Duplex Options: Automatic (standard); Manual (driver support provided); Auto Document Feeder Capacity; O; Envelope Feeder: No; Standard Paper Trays; 2: Input Capacities: Up to 550 sheets Tandem Tray; Up to 100 sheets - MP Tray standard; Up to 10; None transparencies; Up to 1600 + 200 + 40 for
Print Resolution	Black (best): Up to 1200 x 1200 optimized dpi from 600 x 600 input dpi (on Unspecified, Plain, HP Premium Presentation Matte, and HP Brochure Matte); Color (best): Up to 2400 x 1200 optimized dpi from 600 x 600 input dpi (on HP Advanced Photo Papers)		A5 size and larger; tip n of 10 or mailer than A5 size; tip to 1600+200 + 40 sheets tablet; 550 A6 size and larger; tip n of 10 or mailer than A5 size; tip to 1600+200 + 40 sheets tablet; 550 Universal Tray 100 - NP Tray legal; Output Capacities; tip to 500 sheets standard; tip to 50 envelopes; None transparencies; tip to 200 cards; tip to 200 sheets labels; tip to 500 sheets legal
Print Technology	HP PageWide Technology with pigmented inks	What is the barrier	Y3Z64A HP PW Managed Color MFP P77940dns; HP Setup Ink Cartridges (yield after setup ~16000
Print Resolution Technologies	HP PageWide Technology up to 1200 x 1200 optimized dpi from 600 x 600 input dpi	What's in the box	pages CMY and ~20000 K); Installation guide, Support flyer; documentation on CD-ROM; Power cord
Print Cartridges Number	4 (1 each black, cyan, magenta, yellow)	Replacement Cartridges	HP 990AC Black Contract PageWide Crtg (US/CA) (20,000) X4D18AC; HP 990AC Cyan Contract PageWid
Standard Print languages Printer Smart Software Features	THP PCLXL (PCL6), PCL5, native PDF, HP Postscript Level 3 emulation, PJL, JPEG, PCLM HP Trusted Platform Module; HP JetAdvantage Security Manager; HP Web Jetadmin; HP ePrint, Apple		Crtg (US/CA) (20,000) X4D09AC; HP 990AC Magenta Contract PageWide Crtg (US/CA) (16,000) X4D12AC; HP 990AC Yellow Contract PageWide Crtg (US/CA) (16,000) X4D15AC
	AirPrint*, HP Auto-On/Auto-Off technology, HP Color Access Control, HP EasyColor, Front-facing USB printing, store print jobs, print preview, automatic two-sided printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, booklet printing, cover pages, tray selection, scaling, Portrait/Landscape orientation, High Qualify Grayscale and Black Ink Only, General Office/Professional/Presentation dpi print modes, Optional: wireless.	Product Dimensions	W x D x H: 23.8 x 25.7 in x 30.4 in; Maximum: 50.0 x 40.4 x 41.5 in
		Product Weight	181.5 lb1
	HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP Web Jetadmin Software; Printer	Warranty Features	90 day parts only warranty
rinter Management	Administrator Resource Kit for HP Universal Print Driver	Energy Efficiency Compliance	ENERGY STAR® qualified; EPEAT® Gold
Scan Type / Technology	Flatbed, ADF / Contact Image Sensor (CIS)	Control Panel	8.0-in (20.3 cm) Color Graphics Display (CGD) with IR touchscreen; rotating (adjustable angle) display;
ican Resolution	Hardware: Up to 600 ppi; Optical: Up to 600 ppi		illuminated Home button (for quick return to the Home menu); USB High-speed 2.0 port; Hardware Integration Pocket
Scan File Format	Scan File Types supported by included software: Bitmap (.bmp), JPEG (.jpg), PDF (.pdf), PNG (.png), Rich	Display Description	8.0-in (20.3 cm) Color Graphics Display (CGD) with IR touchscreen
scarr ne i ormat	Text (.rtf), Searchable PDF (.pdf), Text (.txt), TIFF (.tif) Front panel applications: Copy, Scan to E-mail with LDAP e-mail address lookup, Scan to Network	Software Included	
Scan Input Modes	Folder, Scan to USB, Scan to Sharepoint. Client applications: EWS, HP Scan App, ADF: 11.7 x 34 in Maximum; 4 x 6 in Minimum; Flatbed: 11.7 x 17 in		HP Device Experience (DXP), HP PCL 6 Print Driver, HP Software Installer/Uninstaller, Mac OS Welcome Screen (Directs users to 123.HP.com or OS App Source for printer software), Online user manuals
Scan Size	Up to 50 ipm (mono and color), LEF*Duplex:	Fonts and Typefaces	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3
can Speed	Up to 35 ipm (mono and color), LEF*		emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at http://www.hp.com/go/laserietfonts
Scanner Advanced Features	Optimize text/picture; Image adjustments; Job build; Output quality setting; Selectable scan resolution 75 to 600 dpi; Auto detect color; Edge Erase; Job notification; Blank page suppression; HP Quick Sets; Scan and save to destinations: network folder, FTP, Sharepoint, USB flash drive, e-mail; see software section for more details.	Compatible Operating Systems	Android, Linux Boss (50), Linux Debian (70, 71.1, 72, 73.7, 47.5, 7.6, 77.7, 8.7, 9.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.10 (19semite, OS X 10.11 E (13.6), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.10 (19semite, OS X 10.11 E (13.6), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.10 (19semite, OS X 10.11 E (13.6), Linux Buntu (13.6), Li
Bit Depth / Grayscale levels	24-bit / 256		(excluding RT OS for Tablets), Windows 7 all 32- & 64-bit editions, Windows 8/8.1 all 32- & 64-bit
Digital Sending Standard Features	Scan-to E-mail with LDAP email address lookup; Scan-to Network Folder; Scan-to USB; Scan-to		editions(excludingRTOSforTablets), Windows Vistaall 32 biteditions (HomeBasic, Premium, Professional, etc.), Windows XP SP3 32-bit editions (XP Home, XP Pro, etc.)
	Sharepoint, Scan to FTP;Send to LAN Fax; Send to Internet Fax; Color Access Control; Native authorization and authentication; Quick Sets; two-sided copying; scalability, image adjustments (darkness, contrast, background cleanup, sharpness); N-up, N or Z-ordering; content orientation; collation; booklet; IO Scan; job build; edge-to-edge; job storage	Compatible Network Operating Systems	Citrix MetaFrame Presentation Server 3.0, Citrix MetaFrame XP Presentation Server (Feature Release 1, 2, and 3), Citrix on Windows Server 2003/2003R2, Citrix on Windows Server 2003/2003R2, Citrix on Windows Server 2003/2003R2, Citrix on Windows Server 2008/2003R2, SP1, Citrix on Windows Server 2008/2003R2, Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0 (Plus
Copy Speed			Feature Pack 2 & 3) for Windows Server 2008 Terminal Services 32- and 64-bit, Citrix XenApp 6.0/6.5
Copy Resolution	Color (A4): 3		[for Windows Server 2008 R2 Terminal Services, 32- and 64-bit], Citrix XenApp 6.0/6.5/7.5 [for Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit], Citrix XenApp 7.5 [for Windows
Maximum Number Of Copies	Black (text and graphics): Up to 600 x 600 dpi; Up to 600 x 600 dpi; Color (text and graphics): Up to 600 x 600 dpi	Server 2012 and 201: R2 Terminal Services,	Server 2012 and 2012 R2 Terminal Services, 64-bit], Citrix XenDesktop 5.6 (for Windows Server 2008 R2 Terminal Services, 32- and 64-bit], Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit], Citrix XenDesktop 7.0/7.5 (for Windows Server 2012 and 2012 R2
Copier Resize	Up to 9999 copies 2		Terminal Services, 64-bit], Novell NetWare 6.5/SP8 Novell Clients www.novell.com/iprint, Novell iPrint
Copier Settings	5 to 400% Two-sided copying, scalability, image adjustments (darkness, contrast, background cleanup, sharpness), N-up, N or 2-ordering, content orientation, collation, booklet, ID Scan, job build, edge-to-edge, job storage		Appliance v1.0, Novell Open Enterprise Server 11/SP1, Novell Open Enterprise Server 2 for Linux, Novell Servers wawn.voell.com/jnnit, Windows Server 2003/2003 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2003 22/64-bit (SP2) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 32-/64-bit (SP2) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/2012 R2 64-bit Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/2012 R2 64-bit Standard/Essential/Datacenter (+ Cluster & Terminal Services)
Fax Speed Fax Resolution	Up to: 33.6 kbps Black (best): Up to 300 x 300 dpi (400 x 400 dpi for received faxes only); Color (best): Up to 300×300 dpi (400 x 400 dpi for received faxes only); Black (standard): 204×98 dpi; Color (standard): Up to 300×300 dpi $(400 \times 400$ dpi for received faxes only)		
Fax Smart Software Features	Stored faxes; Fax archiving; Fax forwarding; Scale to fit; Fax address book; LAN/Internet fax; Fax number confirmation; Holiday fax schedule	Minimum System Requirements	PC: Windows* 10, 8.1, 8, 7: 1.GHz -32-bit or 64-bit processor, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft* Internet Explorer. Windows Vista*: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection,
Fax Features	Fax Memory: Up to 500 pages (black and white); Auto Fax Reduction Supported: Yes; Auto-Redialing; Yes; Fax Delayed Sending; No; Distinctive Ring Detection Supported: No; Fax Forwarding Supported: Yes; Fax Phone TAM Interface Supported: No; Fax Polling Supported: Yes; Goll to receive only); Fax Telephone Mode Supported: No; Junk Barrier Supported: Yes; Maximum Speed Dialing Numbers: Up to 1000 numbers (each with 210 destinations); PC Interface Supported: Yes, HP Software support provided; Remote Retrieval Capability Supported: No; Telephone Handset Supported: Yes		USB port, Microsoft* Internet Explorer 8. Windows* NZ PSP3 or higher (32-bit only); any Intel* Pentium* II, Celeron* or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft* Internet Explorer 8; MAC. Apple* OS X V10.12 Sierra, OS X V10.11 El Capitan, OS X V10.10 Yosemite; minimum 1.2 GB available HD space; Internet required; USB port
Standard Connectivity	2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Hardware Integration Pocket	Power	Power Supply Type: Internal (Built-in) power supply; Power Requirements: Input voltage: 100 to 240 VAC, 50/60 Hz; Power Consumption: 475 watts (printing), 32 watts (ready), 1.4 watts (sleep), 0.2 watts
Network Capabilities	Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx ,	Acoustics	(off)2 Acoustic Power Emissions: 7 B(A) (Print color simplex A4 at 41 ppm)
•	1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPsec (standard)	Operating Environment	
Wireless Capability	Optional, enabled with purchase of a hardware accessory	,	Operating Temperature Range: 15 to 30°C; Recommended Operating Temperature: 17 to 25°C; Storage Temperature Range: Before initial setup (Non-Purged): -40 to 60°C; After initial setup (Purged): 0 to
Mobile Printing Capability	HP ePrint, Apple AirPrint™, Google Cloud Print		60°C. If stored below the lowest specified operating temperature, unit must slowly warm up to an
Memory	Standard: 2816 MB – System Total Standard; 1280 MB on Formatter; 1024 MB on the SCB; 512 MB on the ECB; Maximum: 3844 MB – System Total Standard; 2048 MB on Formatter (with 1024 MB DIMM); 1024 MB or the SCB; 512 MB on the ECB	-	approved operating temperature (HP recommends waiting 24 hours at approved operating temperature prior to using the printer). Non-Operating Humidity Range: 10 to 80% RH; Operating Humidity Range: 10 to 80% RH; Recommended Humidity Operating Range: 30 to 70% RH
Processor Speed	1.2GHz	Security Management	Kerberos authentication, LDAP authentication, 2000 user PIN codes, Network: IPsec/firewall wit Certificate, Pre-Shared Key, and Kerberos authentication, Supports WJA-10 IPsec configuration Plug in
Duty Cycle			802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control List, Hi Trusted Platform Module (TPM) comes standard; Data: Storage Encryption, Encrypted PDF & Email (use:
Recommended Monthly Page Volume	Monthly, letter: Up to 150,000 pages7 2500 to 30,000		FIPS 140 validated cryptographic libraries from Microsoft), Secure Erase, SSL/TLS (HTTPS), Encryptec Credentials; Device: Security lock slot, USB port disablement, HP Security Management: Compatible with
· -			HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessible in
Media Types Supported	Plain paper, HP EcoFFICIENT, HP Premium Presentation Matte 120g, HP Brochure Matte 180g, HP Brochure Glossy, HP Advanced Photo Appers, Light 60-74g, Intermediate 85-95g, Mid-Weight 96-110g, Heavy 111-130g, Extra Heavy 131-175g, Cardstock 176-220g, Labels, Letterhead, Envelope, Heavy Envelope, Preprinted, Prepunched, Colored, Bond, Recycled, Rough	ArcSight and Splunk SIEMs; For more security settings for HP JetAdvantage Security Manager go http://h10032.www1.hp.com/ctg/Manual/	
Media Weight Supported	Tray 1: 60-220 gsm, 300 gsm Photo Paper Only; Trays 2-5: 60-220 gsm; HCI trays 3 & 4: 60-220 gsm		HP PageWide Managed 550-sheet Paper Tray (P1V16A), HP PageWide Managed 550-sheet Paper Tray and Cabinet (P1V17A), HP PageWide Managed 3x550 sheet Paper Tray and Stand (P1V18A), HP
Media Sizes Supported	12 x 18; 11 x 17; RA3; A3; BK: 273 x 394 mm, 270 x 390 mm, 260 x 368 mm; B4 (JIS); Legal; Oficio 216 x 340 mm; Oficio 8.5 x 13; C4; SRA4; RA4 - R; Arch A+R; A4(3; A4 - R; Letter - R; 16K: 197 x 273 mm - R, 195 x 270 mm - R; executive - R; A5 - R; 16K: 184 x 260 mm - R; B5 (JIS) - R; Arch A; Statement; Letter; RA4; A4; 5 x 8; Double Japan Postcard Rotated; 16K: 197 x 273 mm, 195 x 270 mm; 184 x 260 mm; Executive; B5 (JIS); B6 (JIS); 5 x 7; 4 x 6; 10 x 15 cm; A5; Double Japan Postcard Rotated - R; A6; Japanese Postcard; (Lustom-sized media; Envelope; Envelope #10; Envelope D1; Envelope Manarch; Envelope #10; Arch; 5 x 81 dnex card; Double Japan Postcard Rotated - R; A6 lapanese Envelope F1; C4 card; Double Japan Postcard Rotated - R; A6 lapanese Envelope F1; C4 l		PageWide Managed 4000 sheet High-capacity Paper Tray and Stand (P21/19A), HP 128GB Memory Module (WILB49A), HP Internal USB Ports (BS128A), HP Foreign Interface Harnes (BS131A), HP 1 GB 332 144-pin (B00 MHz) DDR3 SDDIMM (ESK4BA), HP Jetdirect 2900nw Print Server (J8031A), HP Jetdirect 3000w NFC/Wireless Accessory (J8030A), HP LaserJet MFP Analog Fax Accessory 500 (CC497A)
		HP Service and Support Options	U9VX9E - HP 3 year Next Business Day Onsite; U9VY0E - HP 4 year Next Business Day Onsite; U9VY1E HP 5 year Next Business Day Onsite
		Learn more at hp.com	

1 With ink installed, no media in trays 2 Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power Consumption and Energy Star TEC values typically based on measurement of 115V device. 3 Speed specifications have been updated to reflect current industry testing methods. 4 Based on standard TTU-T test image #1 at standard resolution. More complicated pages or higher resolution will take longer and use more memory. 5 150 speeds measured using 150/IEC 24734. Excludes first pages for first set of 150 test pages. For details see hp.com/go/printerclaims 6 No heating or fusing warm up time required 7 Durly cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups. 8 HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period. 9 HP SureSupply alerts you when you should replace a print cartridge and helps you purchase locally or via the Internet. For more information, visit hy com/learn/Suresupply. Only available with the printer in the HP Paged Printing Supplies Commands and the standard of the BATEC method with the following possible exceptions: 1 minute or less sleep delay setting, Wi-Fi disabled. 13 Normalized TEC (watt hours per page) BA: 0.388 Wh/page, ES: 0.388 Wh/page, E

